

LITHIONICS BATTERY®

LITHIUM ION IRON PHOSPHATE BATTERY SYSTEMS



MODEL NUMBER:
12V330A-8D-CTRL400

INTERNAL BMS
VERSION



NEVERDIE®

| Item | Description |
|---|--|
| Model | 12V330A-8D-CTRL400 |
| Nominal Voltage | 12.8 |
| Nominal Capacity | 330 |
| Nominal Watt Hours | 4224 |
| Internal Resistance | <300 milliohms |
| Charge | |
| Charging temperature range | 32F/0C to 113F/45C |
| Charge voltage | 14.6 |
| Recommended float charge voltage(for standby use) | 13.4 |
| Recommended charge current* | 165 |
| Allowed max charge current* | 330 |
| Discharge | |
| Discharging temperature range | -4F/-20C to 131F/55C |
| Operating Voltage Range | 11.6 to 13.4 |
| Recommended discharge current* | 330 |
| Max discharge current* | 400 |
| Pulse discharge current | 3300 |
| Discharge cut-off voltage | NeverDie® Power Reserve @ 12.00 Low-Voltage Cut-Off @11.60 |
| Mechanical | |
| Dimensions | Length 23.0" Width 13.0" Height 12.0" |
| Weight | Approx. 115lbs (52.2kg) |
| Storage | |
| Storage Temperature & Humidity Range | < 1 Month -4~95°F (-20~35°C), 45~75%RH |
| | < 3 Months 14~86°F (-10~30°C), 45~75%RH |
| | Recommended storage 59~95°F (15~35°C), 45%RH~75%RH |
| Long Term Storage | If the battery needs to be stored for > 3 months the voltage should be 13.2V (50%SOC), and stored at the recommended storage specifications shown above. Additionally, the battery needs at least one charge & discharge cycle every six months. |
| Self-discharge rate | Residual capacity ≤3% per month; ≤15% per year |
| | Reversible capacity ≤1.5%per month; ≤8% per year |

* Maximum charging and discharging rates apply depending upon the ambient temperature and duty cycle of the system.
UL1973 tests of maximum charge and discharge current were performed at 25°C/77°F

INTERNAL NEVERDIE® FEATURES

- miniBMS® Cell/Module Sensors and Microprocessors with Automatic Cell Balancing
- NeverDie® Power Reserve (Spare Fuel) for Hotel Loads and Worry-Free Power for Engine Cranking
- 100% Pure Copper Power Transmission (No Restrictive Nickel, Aluminum, or MOSFETS)
- UL Approved Temperature Protection System
- UL Approved Fully Redundant Protective Safety Circuits
- Over-Charge, Over-Discharge and Short-Circuit Protection (LVC, HVC, SCC)
- Military Grade/Military Approved Hermetically-Sealed UL508 Approved Gas-Filled Pure Silver-Alloy Contactor with Aux-Contact Monitoring Circuit and Internal Arc-Suppression.
- Available NeverDie® Internal Heating Kit: Permits Charging Operations at -20C/-4F Continuous (Most Models....Please Confirm with Factory)
- Pushbutton Storage Operation



ENERGY

330 CRANKING AMPS

PULSE AMPS: 3300 (1 SEC)

4224 WATT-HOURS

WARNING

1. LITHIUM BATTERIES ARE NOT DESIGNED FOR CHARGING IN SUB-FREEZING TEMPERATURES. CONTACT LITHIONICS BATTERY® FOR DETAILS ON OUR COLD WEATHER PACKAGE.
2. INSTALLATION: IT IS RECOMMENDED THAT BATTERIES BE INSTALLED CABLE OR TERMINAL SIDE UP.

NOTE: CONTACT LITHIONICS BATTERY® FOR A USER INSTALLATION GUIDE & STORAGE PROCEDURES. FOLLOW THE GUIDE TO ENSURE FITNESS OF USE & WARRANTY.

12V STANDARD SERIES